Product Info

Movie CD 1500

Technical Data

Type	-	Home-Cinema-System with active subwoofer system
Engineering Principle	-	Front: 2½-way Bass reflex system
		Center: 2½-way closed system
		Surround: 2-way closed system
		Subwoofer: Bass reflex system
Nom. /Music power handling	-	Front: 80 / 140 watts
		Center: 60 / 100 watts
		Surround: 45 / 100 watts
Musical output	-	Subwoofer: 150 watts
Frequency response	-	Front: 45...25.000 Hz
		Center: 50...25.000 Hz
		Surround: 60...25.000 Hz
		Subwoofer: 25...200 Hz
Crossover frequency	-	Front: 400 / 3.500 Hz
		Center: 400 / 3.500 Hz
		Surround: 3.900 Hz
		Subwoofer: 55...200 Hz (adjustable)
Woofer	-	Front: 2 x 80 mm (3"), aluminum
		Center: 2 x 80 mm (3"), aluminum
		Surround: 1 x 80 mm (3"), aluminum
		Subwoofer: 1 x 220 mm (9"), aluminum
Midrange	-	Front: 2 x 80 mm (3"), aluminum
		Center: 2 x 80 mm (3"), aluminum
Tweeter	-	Front: 1 x Front: 15 mm (1"), aluminum
		Center: 1 x Center: 15 mm (1"), aluminum
		Surround: 1 x Surround: 15 mm (1"), aluminum
Nominal Impedance	-	4...8 ohms
Dimensions (WxHxD)	-	Front: 9 x 103 x 9 cm - (3.5" x 40.6" x 3.5")
		Center: 43 x 9 x 9 cm - (16.9" x 3.5" x 3.5")
		Surround: 9 x 14 x 9 cm - (3.5" x 5.5" x 3.5")
		Subwoofer: 25.5 x 45 x 37 cm - (10" x 17.7" x 14.6")
Weight	-	Front: 8.7 kg
		Center: 3.4 kg
		Surround: 1.3 kg
		Subwoofer: 12.1 kg
Special Features	-	Front:
		Magnetically shielded, Aluminum speaker base plate
		Center:
		Magnetically shielded, Wall brackets included
		Surround:
		Magnetically shielded, Polymer protection, Wall brackets included
		Subwoofer:
		Downfire Woofer, Adjustable phase limiter, Adjustable crossover frequency, Adjustable bass level, SC-technology

Awards:

video Home Vision Preis/Leistung Gut

video Home Vision Testurteil Gut

CANTON®

German loudspeaker tradition